

CHASSISCAB Diesel 2025

Car Code: SCF3005 - 6x4, Rigid Chassis





ENGINE & TRANSMISSION	
Complete kerb mass(kg)	9400
Model	WP12.430E201,6-in-line, water cooled, turbocharger
Power(kw/HP)	316/430 (engine displacemen 11.596L)
Max. Torque/RPM	2000/1000-1400
Model	FAST 12JSD200T-B PTO
Gears	12 forwards & 2 reserve shifts
Max Input Torque (N.m)	2000
Clutch Type	430 diaphragm-spring type
DIMENSION, CAPACITIES & SUSPENSIC	DNS
GVW(Tons)	40 Tons

Overall dimensions(mm)	L 10500 x W 2550 x H 3300
Wheelbase(mm)	4575+1400
Rated RPM	1900 RPM
Emission standard	Euro II
Front axle	HANDE MAN 9500kg
Rear axle	"HANDE MAN16000kg*2, hub reduction axle with inter-wheel differential and different lock Rear axle ratio:4.769"
Brake system type	Drum brake
Service brake	With dual-circuit compressed air brake
Parking brake	Power spring brake acting on rear wheel
Steering Type	ZF8098 technology, integral circulating ball power steering
Chassis Frame	850x300(8+5), double plate chassis frame
Front suspension	Multi-plate leaf spring
Rear Suspension	Multi-plate leaf springs
Tires Type	12.00R24*11
Fuel Tank Capacity	400L Aluminum Alloy Tank
Cabin Type	SHACMAN F300 flat roof sleeper cab
INTERIOR FEATURES & SAFETY	
Hydraulic driver seat	Auto A/C
Hydraulic cab suspension	Reverse buzzer
Manual cab titling	Manual rear view mirror

ABS

EXTERIOR FEATURES	
Metal bumper	Oil pan protection
Fuel anti-theft system	Battery anti-theft system
Extra fuel filter	Front and rear light protection