

SHACMAN F3000 6×4 Tractor Head MY25 TRACTORHEAD Diesel 2025

Car Code: SHF3005 - 6×4, Tractor Head





ABS











ENGINE & TRANSMISSION	
Model	WP12.430E201,6-in-line, water cooled, turbocharger
Power(kw/HP)	316/430 (engine displacement 11.596)
Max. Torque/RPM	2000/1000-1400
Rated RPM	1900 RPM
Emission standard	Euro II
Model	FAST 12JSD200T-B+PTO
Max Input Torque (N.m)	2000
DIMENSION, CAPACITIES & SUSPENSI	ONS
Overall dimensions(mm)	L 7000 x W 2550 x H 3500
Wheelbase(mm)	3175+1400
Complete kerb mass(kg)	9500
GCW(Tons)	90 Tons
Gears	12 forwards & 2 reserve shifts
Clutch Type	430 diaphragm-spring type
Front axle	HANDE MAN 9500kg
Rear axle	"HANDE MAN16000kg*2, hub reduction axle with inter-wheel differential and different lock Rear axle ratio:4.266"
Brake system type	Drum brake

Front axle	HANDE MAN 9500kg
Rear axle	"HANDE MAN16000kg*2, hub reduction axle with inter-wheel differential and different lock, Rear axle ratio: 4.266 "
Brake system type	Drum brake
Service brake	With dual-circuit compressed air brake
Parking brake	Power spring brake acting on rear wheel
Steering Type	ZF8098 technology, integral circulating ball power steering
Chassis Frame	850x300(8+7), double plate chassis frame
Front suspension	Multi-plate leaf spring
Rear Suspension	Multi-plate leaf springs
Tires Type	12.00R24*11
Fuel Tank Capacity	400L Aluminum Alloy Tank
Fifth wheel	90 #
Cabin Type	SHACMAN F300 flat roof sleeper cab

INTERIOR FEATURES & SAFETY Air driver seat Auto A/C Hydraulic cab suspension Reverse buzzer Manual cab titling Manual rear view mirror

EXTERIOR FEATURES		
Steel bumper	Oil pan protection grid	
Fuel anti-theft system	Battery anti-theft system	